



**INSTALLATION INSTRUCTIONS  
PLEASE READ THE FOLLOWING  
INSTRUCTIONS BEFORE  
INSTALLING YOUR NEW AIR CLEANER**

**CATALOG #1235, #1236, #4235, #4236, #4237 and #4238**

**MODEL:** Pro-Flo/Elite Oval Air Cleaners -  
Single carb (#1236, #4236 & #4238) and Dual carb (#1235, #4235 & #4237)

**INSTALLATION INSTRUCTIONS:**

1. Install suitable air horn gasket and carburetor stud (not supplied) on carburetor(s) and place air cleaner base over carburetor.
2. For single carb models (#1236, #4236 & #4238), thread the special bracket on the carb stud until the two studs protrude through the top of the air cleaner by about 1/2". Bracket must be positioned to clear carburetor choke linkage.
3. Install filter and air cleaner lid, checking for clearance between the carb stud and lid. Trim carb stud if necessary.

For carburetors with tall bowl vent tubes, it may be necessary to purchase Edelbrock air cleaner spacer #8092. Vent tube to air cleaner clearance should be no less than 1/8".

**MAINTENANCE:**

This pre-oiled gauze element can be cleaned and re-oiled as needed to extend its filtering efficiency. Simply wash element in hot soapy water and allow to dry, then apply a light aerosol oil. Replacement filters (Edelbrock #1220) are available through your dealer. Replacement knurled nuts for Elite Series Oval Air Cleaners #4235, #4236, #4237 & #4238 are available as Edelbrock #4219.