



## INSTALLATION INSTRUCTIONS EDELBROCK HEAT INSULATOR CARB GASKET #9265

- CONTENTS: 1- Square-bore gasket (0.300" thick)  
4- 5/16" x 1-3/4" carburetor studs
- DESCRIPTION: The Edelbrock Square-bore Heat Insulator Gasket is designed to prevent percolation on Edelbrock Performer Series carburetors exposed to extreme underhood temperatures. This gasket features an open center which will allow open plenum *Torker* and *Victor* style manifolds to seal properly to the carburetor. For divided plenum manifolds such as the Performer series, use gasket #9266, which has a center divider.
- INSTALLATION: Prior to installation, check air cleaner-to-hood clearance to ensure that additional height of heat insulator gasket will not cause interference. Remove air cleaner and all attachments to the carburetor such as fuel line, throttle linkage, and vacuum lines. Be sure to note the position or tag each piece to facilitate re-installation. Remove the carburetor and set it aside, then remove the old base gasket and any additional plates, such as Edelbrock square-bore adapter #2732. Remove the short carb studs and install the longer studs. Install the #9265 heat insulator gasket directly against the manifold, then replace the carb and all other connections. Note that gasket #9265 is rigid enough to replace square-bore adapter plate #2732, if required.
- CAUTION: This Gasket (#9265) is intended for use on Edelbrock Performer Series Carburetors and Edelbrock open plenum manifolds only. It is not for stock manifolds which have exhaust gas openings at the carb flange.

This gasket has only the large bolt pattern. If the small bolt pattern is required (to facilitate throttle bracket mounting, for instance), you may drill a hole or file a slot in the gasket using your carburetor or your old gasket as a guide.

Catalog #9265  
Rev. 8/08 - AJ/mc

©2008 Edelbrock Corporation  
Brochure #63-9265



## INSTALLATION INSTRUCTIONS EDELBROCK HEAT INSULATOR CARB GASKET #9265

- CONTENTS: 1- Square-bore gasket (0.300" thick)  
4- 5/16" x 1-3/4" carburetor studs
- DESCRIPTION: The Edelbrock Square-bore Heat Insulator Gasket is designed to prevent percolation on Edelbrock Performer Series carburetors exposed to extreme underhood temperatures. This gasket features an open center which will allow open plenum *Torker* and *Victor* style manifolds to seal properly to the carburetor. For divided plenum manifolds such as the Performer series, use gasket #9266, which has a center divider.
- INSTALLATION: Prior to installation, check air cleaner-to-hood clearance to ensure that additional height of heat insulator gasket will not cause interference. Remove air cleaner and all attachments to the carburetor such as fuel line, throttle linkage, and vacuum lines. Be sure to note the position or tag each piece to facilitate re-installation. Remove the carburetor and set it aside, then remove the old base gasket and any additional plates, such as Edelbrock square-bore adapter #2732. Remove the short carb studs and install the longer studs. Install the #9265 heat insulator gasket directly against the manifold, then replace the carb and all other connections. Note that gasket #9265 is rigid enough to replace square-bore adapter plate #2732, if required.
- CAUTION: This Gasket (#9265) is intended for use on Edelbrock Performer Series Carburetors and Edelbrock open plenum manifolds only. It is not for stock manifolds which have exhaust gas openings at the carb flange.

This gasket has only the large bolt pattern. If the small bolt pattern is required (to facilitate throttle bracket mounting, for instance), you may drill a hole or file a slot in the gasket using your carburetor or your old gasket as a guide.

Catalog #9265  
Rev. 8/08 - AJ/mc

©2008 Edelbrock Corporation  
Brochure #63-9265